




ALUMINIUM COMPOSITE MATERIAL  
**etalbond®**



**BARRE TONDE IMPERIALI**

**Lega: 2007 , 2011 , 6012 , 6082 , 6262**

Diametro mm	Lunghezza *	Lega <b>2000</b> <b>serie</b> <b>T3 , T8</b>	Lega <b>6000</b> <b>serie</b> <b>T3,T8,T6,T9</b>	Peso Lineare g/m +/-
----------------	-------------	---	---	-------------------------------

<b>TRAFILATO</b> Ø 1/2 - 2 "  Tolleranze e Specifiche in accordo a EN - 754 , DIN 1798	1/2	3 m	√	6262 e 6082 su richiesta	
	9/16	3 m	√		
	5/8	3 m	√		
	11/16	3 m	√		
	3/4	3 m	√		
	7/8	3 m	√		
	15/16	3 m	√		
	1	3 m	√		
	1 1/8	3 m	√		
	1 3/16	3 m	√		
	1 1/4	3 m	√		
	1 3/8	3 m	√		
	1 1/2	3 m	√		
	1 5/8	3 m	√		
	1 3/4	3 m	√		
	1 7/8	3 m	√		
2	3 m	√			

\* La cianfrinatura standard è a 30° gradi da un lato e dritta dall'altro  
 A richiesta di può cianfrinare a 45°

<b>ESTRUSO</b> Ø 2 1/8 - 4 3/4 "  Tolleranze e Specifiche in accordo a EN - 755 , DIN 1799	2 1/8	3 m	√	6262 e 6082 su richiesta	
	2 1/4	3 m	√		
	2 3/8	3 m	√		
	2 1/2	3 m	√		
	2 5/8	3 m	√		
	2 3/4	3 m	√		
	3	3 m	√		
	3 1/4	3 m	√		
	3 1/2	3 m	√		
	3 3/4	3 m	√		
	4	3 m	√		
	4 1/4	2,90 m	√		
	4 1/2	2,30 m	√		
	4 3/4	2,10 m	√		

